

Optimization Of Turning Parameters Of EN-8 Steel Cylindrical Rods Using Taguchi Methodology

Ramya.R¹, Supritha.M², Ankit Kumar Jha³, Abhijeet Singh Babu⁴, Akash Gowda⁵

¹ Asst. Professor, Department of Mechanical Engineering, Sri Sairam College of Engineering,
Bengaluru..

^{2,3,4&5} UG SCHOLAR Department of mechanical Engineering, Sri Sairam College of Engineering,
Bengaluru.

Abstract:

Surface roughness is an important parameter for ensuring the dimension geometry is within the permitted tolerance. The ideal surface roughness is determined by optimal turning parameter of EN-8 steel cylindrical rods. Recently EN-8 steel finding many applications like shaft, axle, gears and Fasteners due to their high hardness, strength and weight ratio. Optimum machining parameters of turning operations are greatly influenced with concern along with manufacturing environment. In this experimental work turning parameters on EN-8 steel with different cutting parameters like cutting speed, feed and depth of cut are greatly influenced by response parameters. The experimental design was formed based on Taguchi's Technique, An orthogonal array and Analysis of Variance (ANOVA) are employed to investigate the Turning conditions and machining was done using coated tool insert.

Keywords: EN-8, Turning parameters, Taguchi DOE, S/N ratio, ANOVA.

1.Introduction:

Turning is one of the most basic machining processes which work is rotated while a single point cutting tool is moved parallel to the axis of rotation. In turning process parameters such as cutting speed, feed and depth of cut, number of passes as well as use of cutting fluids will impact the production cost and machine qualities like surface roughness and material removal rate. Proper selection of cutting parameters can obtain a minimum cost, maximum material removal rate, longer tool life and better surface roughness. (1) Matsumura T, Obikawa et al (2004) performed turning operation and study the machinability of steel and give key note to determination of optimal cutting conditions for surface finish obtained in turning using design of experiments for carbide coated tool. (2) Sukker G. (2005) gives analyzing the chip formation & chip geometries during high speed machining for orthogonal cutting conditions and obvious that achievements of proper surface finish of the manufactured parts are desirable and essential in some applications. (3) Ghosh, Amitabh, Ashokkumar et al (2006) have discussed the surface finish in machining and have indicated that the resultant roughness produced by a machining operation is the combined effect of two independent quantities namely ideal roughness and natural roughness.

According to them, ideal roughness is a result of the geometry of the tool and the feed.(4)Vikram Kumar, CH R. and Ramamoorthy, B et al (2007) have dealt with Performance of coated tools during hard turning under minimum fluid application. Further (5) Sharma, D.K.and Dixit U.S.(2007) have compared the dry and air-cooled turning of grey cast iron with mixed oxide ceramic tool.(6)Gokkaya, Hasan, Nalbant, Muammer et al(2008) have studied The effects of cutting tool geometry and processing parameters on the surface roughness of AISI 1030 steel. However, Isik, Yahya et al (2008) have investigated the machinability of tool steels in turning operations(7) Tamilmani (2007) has shown that the depth of cut had contributed 15% in providing lower surface finish. (8) Aslantas, Ucan,Goek et al (2007) also report the possibility of finish turning of steel with CNB inserts under high speeds.(9)Ersan Aslan et al. (2007) has shown that the optimized machining parameters while machining AISI 140 steel with ceramic tool and shown that cutting speed, feed rake and depth of cut inter actions have significant influence on surface roughness. (10)Paulo Davim (2009) express a note on the determination of optimal cutting conditions for surface finish obtained in turning using design of experiments for carbide coated tool turning Design of experiment (DOE) is a structured, organized method used to determine the relationship between the different input factors (Xs) and the outputs (Ys) of a process. Design of experiment involves designing a set of experiments, in which all relevant factors are varied systematically. When the results of these experiments are analyzed, they help to identify the factors that most influence the results, interactions and synergies between factors, and optimal conditions. Experimental design is a strategy to gather knowledge based on the analysis. This study excludes and fixes less influencing tool wear and many others factors as they were discussed in details the researchers and got optimized earlier. Hence the contributions by the researchers are considered as best suited and kept at constant and referred as least influencing factors for simultaneous optimization.

2.Methodology

1. State the problem
2. State the objectives of experiments
3. Select the factors that may influence the selected quality characteristics
4. Identify quality and noise factors
5. Select levels for the factors
6. Select appropriate orthogonal array
7. Select interactions that may influence the selected quality characteristics
8. Conduct the tests described by trails in orthogonal array
9. Analyze and interpret results of the experimental trails
10. Conduct confirmation experiment

2.1 Taguchi Design of Experiments

Taguchi method is a powerful tool in quality Optimization makes use of a special design of orthogonal array (OA) to examine Number of experiments used to design the orthogonal array for 3 factors and 3 levels of turning parameters.

$$\begin{aligned}\text{Minimum experiments} &= [(L-1) \times p] + 1 \\ &= [(3-1) \times 3] + 1 = 7 \approx L_9\end{aligned}$$

2.2 Analysis of Variance

In statistics, Analysis of variance (ANOVA) is a collection of statistical models, and their associated procedures, in which the observed variance in a particular variable is partitioned into components attributable to different sources of variation. In its simplest form, ANOVA provides a statistical test of whether or not the means of several groups are all equal, and therefore generalizes t-test to more than two groups. Doing multiple two-sample t-tests would result in an increased chance of committing a type I error. For this reason, ANOVAs are useful in comparing two, three, or more means.

The F-test

The F-test is used for comparisons of the components of the total deviation. For example, in one-way, or single-factor ANOVA, statistical significance is tested for by comparing the F test statistic

3.Result and discussion

Surface Roughness

After conducting the experiments on turning operations of EN-8 steel rods(diameter 22 and 100mm length)with different turning parameter and predict the lower surface roughness

Surface roughness

1. Spindle speed is a dominating parameter to produce lower Surface roughness in turning process.
2. The optimum parameter of turning operation of EN-8 steel plates are 225m/min of cutting speed,0.2mm/rev of Feed and 0.5 mm Depth of cut.

3. However EN-8 Steel plate having good machinability characteristic and Produce reasonable surface finish.
4. Obtained Good surface integrity and minimum wear occur during turning operation of EN-8 steel plates.
5. During turning process all parameters are interact and dependant able in turning operation.

CONCLUSION

After conducting the experiments of turning parameters on EN-8 steel rods and optimum parameters of surface roughness is given below

1. Spindle speed is a dominating parameter for achieving lower surface roughness during turning of EN-8 steel rods.
2. The optimum parameter of surface roughness of EN-8 steel rod are 225m/min of cutting speed, 0.2 mm/rev of Feed and 0.5 mm Depth of cut.
3. However EN-8 Steel plate having good machinability characteristic and Produce reasonable surface finish.

REFERENCES

- (1) Matsumura, T., Obikawa, T., Usui, E (2004). An adoptive prediction of machining Accuracy in turning operation. Transactions of NAMRI/SME 22,305-312.
- (2) Sutter G (2005) Chip geometries during High speed machining for Orthogonal cutting conditions Int j Mach tools manufacturing 45(6):719-729.
- (3) Ghosh, Amitabh and Malik, Ashok Kumar, "Manufacturing Science"; East-West Press Private Limited, New Delhi-1985
- (4) Kumar Vikram, R. CH and Ramamoorthy, B., "Performance of coated tools during hard turning under minimum fluid application" Journal of Materials Processing Technology 185 (2007) 210-216.
- (5) Sarma, D.K and Dixit, U.S , "A comparison of dry and air-cooled turning of grey cast iron with mixed oxide ceramic tool", Journal of Materials Processing Technology 190 (2007) 160-172.

- (6) Hasan and Nalbant, Muammer, “The effects of cutting tool geometry and processing parameters on the surface roughness of AISI 1030 steel” Gokkaya, Materials and Design 28 (2007) 717–721.
- (7) Singh, D., &Rao, P. A. (2007). Surface roughness prediction model for hard turning process. The International Journal of Advanced Manufacturing Technology, 32(11–12), 1115–1124.
- (8) Singh, D., &Rao, P. A. (2007). Surface roughness prediction model for hard turning process. The International Journal of Advanced Manufacturing Technology, 32(11–12), 1115–1124.
- (9) ErsanAslam, Neeipcamuscu and burak Birgoran, “Design Optimization of cutting parameter when turning hardened AISI 4140 (63HRC) with Al2O3 + TiCN mixed ceramic tool, International Journal of Materials and design Volume 28, Issue, 2007PP, 1618-1622.
- (10) Paulo Davin “The study of high speed fine turning of austenitic stainless steel”, Journal of Achievements in Materials and Manufacturing Engineering, vol-27(2008).