

Analysis of Eeg Signal Using Ssvep For Bci Interface: A Review

Ruchika Thakur

Asst.Professor,
Lovely Professional University
Phagwara, Punjab, India.
ruchika.24906@lpu.co.in

Bhupinder Kaur

Asst.Professor,
Lovely Professional University
Phagwara, Punjab, India.
bhupinder.23611@lpu.co.in

Abstract—This paper shows a SSVEP based Brain Computer Interface (BCI) frameworks which are suggested to enable handicapped individuals who are unequipped for making engine reaction to speak with PC utilizing mind signal. The point of BCI is to decipher cerebrum movement into computerized structure which goes about as a direction for a PC. One key test in ebb and flow BCI look into is the way to separate highlights of arbitrary time-differing EEG sign and its grouping as precisely as would be prudent. Highlight extraction strategies are utilized to extricate the highlights which speak to an exceptional property acquired from example of cerebrum signal. Prior EEG examination was limited to visual assessment as it were. The visual assessment of the sign is exceptionally abstract and barely permits any institutionalization or measurable examination. Thus, a few unique methods were proposed so as to evaluate the data of the mind signal. Numerous straight and non-direct techniques are existing for extraction. The motivation behind this is to give a concise prologue to the EEG sign and BCI framework. It additionally remembers an audit for the ordinary techniques that are utilized for include extraction of the sign.

Keywords—Steady State Visual Evoked Potential (SSVEP); Feature Extraction; fMRI (Functional Magnetic Resonance Imaging); Brain Computer Interface (BCI); Electroencephalogram (EEG); MEG (Magneto Encephalography).

I. INTRODUCTION

An immediate mind PC interface is a gadget that furnishes the brain with another, non-strong correspondence and control channel. BCI framework enables a subject to send directions to an outer gadget by utilizing cerebrum signal. BCI means can be examined as the main path through which individuals influenced by engine incapacities can convey their musings. It is useful to help patients with disabled engine capacities, for example, totally deadened patients with ALS [1, 2]. The point of BCI is to decipher cerebrum movement into advanced structure which goes about as a direction for a PC. One key test in ebb and flow BCI examine is the manner by which to extricate highlights of irregular time-differing EEG flag and characterize the sign as precisely as conceivable [1]. The accomplishment of this system relies upon the determination of techniques to process the cerebrum flag in each stage.

SSVEPs are the responses that are propelled in the mind when the individual is apparently

centering his/her thought on a Repetitive Visual Stimulus (RVS) that is blazing at repeat 6Hz or above [4].

The signals are strong in occipital part of the brain and are almost sinusoidal waveform having the same key recurrence as the boost. By integrating the decisive recurrence of the SSVEP to one of the rise frequencies visible is to identify the objective chosen by the patient EEG.

II. BRAINSAMPLES

The human mind is a tricky framework, between guild of abundance of neurons which displays rich spatiotemporal elements. There are a few obtrusive just as non-intrusive systems for mapping cerebrum signals, for example, EEG(Electroencephalogram), Electrocorticography. Among all the non-obtrusive strategies for analyzing human mind, an immediate proportion of cortical action with a fleeting goals of not as much as millisecond is given EEG [3]. EEG strategy can likewise be utilized to remove the highlights of the cerebrum signal regardless of whether the subject isn't in a state to go to the improvements.

In 1929 Hans Berger has recorded the principal of human cerebrum. Beforehand, its investigation was limited to visual examination as it were. The visual assessment is exceptionally abstract and scarcely permits any institutionalization or factual examination. The conventional strategies are exceptionally dull and tedious [4]. Thus a few systems were proposed so as to evaluate the data of cerebrum signal

The idea of these signals is exceptionally non-definite, irregular, noncrenated. The wounds in cerebrum, any such infection or manifestation can be recognized Electroencephalography (EEG). It is additionally utilized in distinguishing numerous maladies related to nervous system science, for example, Seizure issue like epilepsy, rest issue like Narcolepsy, tumor, gloom and different issues which are related with injury (stress) [5]. The follows are diverse for various mind exercises. Utilizing signal preparing procedures mind action of an ordinary and irregular individual can be recognized effectively.

III.Revelation of EEG signal

For the most part, the signal experiences low signal-to-noise proportion of any evoked reaction which gets placed inside on-going foundation movement. Different data signal isconsolidating with different antiquities and impedances while recording the signal[6]. Due to change in ionic current inside the neurons of the brain the EEG measures voltage also get changed. Be that as it may, it conferslow quality signal as the signs need to cross the scalp, skull, and numerous different layers. This signify EEG flags that take account of electrical action from the scalp with electrodes placement are feeble, difficult to obtain and of low quality. This method is additionally gravely influenced by foundation clamor produced either inside the brain or remotely over the scalp. Relevant categories of different bands are detailed below.




Figure 3.1: Range of Brain Waves in human brain

A. Signal Resolution

The idea of EEG signals is extremely perplexing, non-connected and arbitrary. The attributes/highlights of EEG rely upon a few factors, for example, the personal himself, age and the psychological condition of subject [5]. Subsequently, considerate the conduct and elements of synapses includes numerous type of non-Linear strategies whose result is identified with the physiological experience. A few strategies have been proposed in writing to analyze the shrouded dynamical highlights and unexpected changes that can happen.

IV. BCI Structure

A BCI framework consists of four stages i.e. Signal Acquisition, Signal Pre-Processing unit, Feature Extraction & classification.




Figure 4.1: Schematic overview of a BCI system (Wolpaw et al. [20]).

B. Signal Procurement and Signal Pre-Processing

Electroencephalography (EEG) is an electrophysiological strategy used to evaluate the electrical activity in the brain. EEG signs are effectively recorded in a non-obtrusive way through anodes put on the scalp, for which that reason it is by a long shot the most far reaching recording methodology. EEG measures voltage get changed because of change in ionic current inside the neurons of the brain. After acquisition Signals are to be pre-processed. The obtained signals are contaminated by artifacts and clamor. The EEG signals are to be transformed from spatial domain to frequency domain and also detect eye blinking with a peak pulse from spatial domain. After detecting suitable recognized frequency from eye winking they get transformed into corresponding command. This method is additionally gravely influenced by foundation clamor produced either inside the brain or remotely over the scalp.

TABLE I. DIFFERENT BRAIN RHYTHMS

RHYTHYM	FREQUENCY RANGE (Hz)	AMPLITUDE (μ v)	STATE OF MIND
Delta	Up to 4	(20-200)	sleep
Theta	4-8Hz	More than 20	Creative state, drowsiness
Alpha	8-12Hz	30-50	Day dreaming
Beta	15-20Hz	5-30	Active thinking, problem solving
Gamma	Above 31	≥ 5	Mechanism of consciousness
		$\geq$	

The EEG signs can be determined either monopolarly with all cathodes referenced to same area (for occurrence to ears, to nose, to the area amongst Fz and Cz, or to Iz), or bipolarly with terminal sets. The inferred signs can be further sifted spatially with basic normal reference channel (CAR), little Laplacian channel, or expansive Laplacian channel to enhance signal quality.




Figure 4.2: International System of Electrodes (10-20)

The following stage includes the pre-handling of the sign incorporates signal separating, signal cutting, sufficiency mount, and confirmation of master marks, antique recognition, equate strategies and sign division. The procurement of Electroencephalography signal is essentially done in time area. The sign highlights, its attributes and the data needed from the sign are smothered by clamor. So as to extricate the equivalent, signal preparing is done to separate the highlights of the sign as a component of time or/and recurrence.

A. Visual Evoked Potentials (VEPs)

VEPs are brain movement regulations that happen in the visual cortex subsequent to accepting a visual jolt. These adjustments are generally simple to distinguish following the sufficiency of VEPs increments gigantically as the jolt is drawn nearer to the focal visual field.

B. Steady State Visual Evoked Potentials (SSVEP)

Steady State evoked potential are inspired by the same visual boost. The brain responds straightforwardly to glinting, if individual take a gander at the article which is flickering with some recurrence, then the BCI distinguishes the objective through SSVEP highlights investigation containing same recurrence.

The frequencies of the jolts utilized for SSVEP impelling shift as a part of various studies. In

late experimental distributions creators have considered even the frequencies underneath 2 Hz for delivering enduring state reaction (Xia et al. [21]). To be specific these sorts of incitement summon transient VEPs yet in altered rate which delivers an intermittent reaction that can be treated with the same handling/discovery techniques as SSVEP. In recent review of the stimulation methods for SSVEP eliciting the specified range of stimuli frequencies is 1 to 100 Hz.




Figure 4.3: Diagram of a SSVEP BCI (Chumerin et al. [21]).

A steady state visual evoked potential (SSVEP) is an exogenous reaction to a redundant ocular boosts which typically sways at the central and consonant frequencies of the glinting jolt.

SSVEP are utilized as a control signal as a part of BCI in light of the fact that they can offer the client to choose among a few summons, and in this manner can be utilized to drive a BCI based menu (Xia et al. [21]). Every alternative/summon in such menu is connected with one of the dull visual boosts displayed to the client. Singular boosts can contrast from each other just by their reiteration recurrence. As all boosts are all the while exhibited, the client can centre the visual consideration on the particular one, evoking the relating SSVEP reaction in the EEG measured over the essential visual cortex, which triggers the related menu choice. This depends on the way that the SSVEP sufficiency is more noteworthy for the went to boosts than for the unattended ones, notwithstanding when the jolts are exhibited in the same locale of visual field (Xia et al. [21], Chumerin et al. [2]).

IV. CHALLENGES

Due to characteristic restraint like time reliance, huge elements of highlight vector set, suspicious; capture brain signals from correct position is bit challenged. To overcome this a time-space framework has designed. EEG being a non-intrusive method for example signals captured from scalp through cathode electrode placement is one of the reason that swift agitation. Ancient rewrites discovery and expulsion is the primary continuous test for the designers nowadays. Acknowledgment impalement of the sign with enormous measure of potential highlights extricated from the sign with least computation.

VI. CONCLUSION

The research shows that EEG sign enable us to analyze the psychological states and different neural ailments. The signals are emotional, not connected in nature and are examined as a disorganized sign. As indicated by the audit, a great deal of progress should be done to deliver a framework that can be worked in genuine condition. Diverse sign preparing systems straight and nonlinear, time area, recurrence, time-recurrence and continuum recurrence

space procedures have been examined. Among all the straight strategies the exactness of Wavelet Packet Decomposition in continuum recurrence area is accounted for to yield preferred execution over the other extant procedures. The techniques provide better outcomes for the occasions which can't be identified by investigation of EEG signal visualization, customary and straight sign preparing strategies. The utilization of non-straight techniques comprehends the complex physiological occasions like disordered conduct and abrupt advances that happen in the cerebrum.

REFERENCES

- [1] Shiliang Sun and Jin Zhou," A Review of Adaptive Feature Extraction and Classification Methods for EEG-Based Brain- Computer Interfaces," in IEEE Joint Conference (IJCNN) on Neural Networks International, pp. 1746 – 1753, 2014.
- [2] Dave P. Burke, Simon P. Kelly, Philip de Chazal and Ciarán Finucane, "A Parametric Feature Extraction and Classification Strategy for Brain-Computer Interfacing," IEEE Transactions on Neural Systems And Rehabilitation Engineering, Vol. 13, No. 1, pp. 1534-4320, March 2005.
- [3] Pari Jahankhani, Vassilis Kodogiannis and Kenneth Revett," EEG Signal Classification Using Wavelet Feature Extraction and Neural Networks," IEEE John Vincent Atanasoff JVA International Symposium on Modern Computing, pp. 120 – 124, Oct. 2006.
- [4] Aswathy Madhu, Jayasree V K and Vinu Thomas,"A Survey Paper on Time Frequency Analysis of EEG Signal," Progress In Science and Engineering Research Journal, Vol.02, pp. 046- 051, 2013.
- [5] D. Puthankattil Subha, Paul K. Joseph, Rajendra Acharya U, Choo Min Lim," EEG Signal Analysis: A Survey," Springer Science vol.34, pp.195–212, 2007.
- [6] Amjed S. Al-Fahoum and Ausilah A. Al-Fraihat, "Methods of EEG Signal Features Extraction Using Linear Analysis in Frequency and Time-Frequency Domains," ISRN Neuroscience, Hindawi Publishing Corporation, Article ID 730218, 2014.
- [7] Robert Jenke, Angelika Peer and Martin Buss," Feature Extraction and Selection for Emotion Recognition from EEG," IEEE Transactions on Affective Computing, pp.1949- 3045, 2013.
- [8] N.A. Md Norani, W. Mansor, L.Y. Khuan," A Review of Signal Processing in Brain Computer Interface System," IEEE EMBS Conference on Biomedical Engineering & Sciences, pp. 443 – 449, Nov. 30 2010-Dec. 2 2010.
- [9] Abdul- Bary Raouf Suleiman, Toka Abdul-Hameed Fatehi," Features Extraction Techniques of EEG Signal For BCI Applications," Comp. and Information Engg. Dept. College of Electronics Engg., 2011.
- [10] Mehdi Hoodgar, Mohammad Mehrani, Amin mehranzade1, Faraz Forootan, " Proposing an Effective Feature Extraction Model for EEG Signals to Enhance Quality of Hand's Motion Detection," Journal of Academic and Applied Studies, Vol. 3(2) , pp. 1-19, February 2013.
- [11] Javier Castillo, Sandra M"uller, Eduardo Caicedoy, and Teodiano Bastos"" Feature Extraction Techniques Based on Power Spectrum for a SSVEP-BCI, " IEEE International Symposium on Industrial Electronics (ISIE), pp. 1051 – 1055, June 2014.
- [12] S. Sanei and J. Chambers, "EEG Signal Processing," John Wiley & Sons Ltd, The Atrium, Southern Gate, Chichester, Chichester, West Sussex PO19 8SQ, England,

ISBN-13 978- 0-470-02581-9, 2007.

- [13] M. Rajya Lakshmi, Dr. T. V. Prasad, Dr. V. Chandra Prakash, “ Survey on EEG Signal Processing Methods,” International Journal of Advanced Research in Computer Science and Software Engineering, Volume 4, Issue 1, January 2014.
- [14] Alexandros T. Tzallas, Markos G. Tsipouras and Dimitrios I. Fotiadis,” The Use of TimeFrequency Distributions for Epileptic Seizure Detection in EEG Recordings,” IEEE Annual International Conference EMBS Cité Internationale, August 2007.
- [15] Wu Ting, Yan Guo-zheng, Yang Bang-hua, Sun Hong,” EEG feature extraction based on wavelet packet decomposition for brain computer interface”, ELSEVIER, Measurement 41, pp. 618–625, 2008.
- [16] JR. Panda, P.S. Khobragade, P.D. Jambhule, S. N.Jengthe, P.R.Pal, T.K. Gandhi,” Classification of EEG Signal Using Wavelet Transform and Support Vector Machine for Epileptic Seizure Diction”,IEEE International Conference on Systems in Medicine and Biology, pp. 16-18, December 2010.
- [17] Shiliang Sun, Changshui Zhang,” Adaptive feature extraction for EEG signal classification,” Springer Science International Federation for Medical and Biological Engineering, Aug. 2006.
- [18] Vahid Abootalebi, Mohammad Hassan Moradi, Mohammad Ali Khalilzadeh,” A new approach for EEG feature extraction in P300-based lie detection”, ELSEVIER, computer methods and programs in biomedicine, pp. 48–57, 2009
- [19] Mandeep Singh, Mooninder Singh, Surabhi Gangwar,” Feature Extraction from EEG for Emotion Classification,” IJITKMI, Vol.7, No.1, pp. 6-10, December 2013.
- [20] Wolpaw, J. R., Birbaumer, N., McFarland, D. J., Pfurtscheller, G., and Vaughan, T. M. (2002). Brain-computer interfaces for communication and control. Clin Neurophysiol, 113(6):767–91. 1388-2457 Journal Article Review.
- [21] ZhuoXu, Jie Li, RongGu, and Bin Xia Steady-State Visually Evoked Potential (SSVEP)-Based brain-Computer Interface (BCI): A Low-Delayed Asynchronous Wheelchair Control System. T.Huang et al. (Eds.): ICONIP 2012, Part I, LNCS 7663, pp. 305–314, 2012. © Springer-Verlag Berlin Heidelberg 2012.