

An Experimental Review Of Electro-Optic Of Multifunctional Nitrideproperties

Smriti Sihag

ABSTRACT

The push towards scaling down and higher speeds in electronic gadgets has prodded a quest for the recognizable proof and improvement of new multifunctional materials. Materials displaying more than single electrical, optical, attractive, flexible, or other trademark reaction, are known as multifunctional materials. These materials give the plausibility of incorporating different practical properties, alongside altogether new properties emerging from cross-coupling, into a solitary framework. Such multifunctional materials can be arranged into countless frameworks including compound semiconductors, weaken attractive semiconductors, gigantic magneto resistive materials, and magneto-electric multiferroic materials. As a particular case of how multifunctional materials can be utilized to grow new gadgets, we consider new compound semiconductors for optoelectronic applications. Si, basic semiconductor, was vital for building the cutting edge electronic industry. Anyway Si is an aberrant band hole semiconductor and in this manner isn't a proficient light producer or safeguard. Photovoltaic and optoelectronic gadgets require a solid interchange among photons and electrons. Direct bandgap semiconductors are progressively appropriate for such applications which show solid ingestion or outflow for the ideal electromagnetic unearthly range. III-V and II-VI compound semiconductors are generally utilized in optoelectronic gadgets for example infrared and obvious light transmitting diodes (LEDs), optical fiber interchanges and high proficiency sun powered cells, unequivocally as a result of the more grounded coupling between the semiconducting and optical properties in these materials.

KEYWORDS:Electro-Optic, Magneto- Dielectric Properties, Multifunctional Nitride, photons and electrons.

INTRODUCTION:

As a further model, transistors dependent on semiconducting Si are utilized for information handling, while information stockpiling is practiced utilizing ferromagnetic hard drives with the

attractive data being extricated utilizing attractive multilayers GMR (Giant Magneto opposition) structures as read heads, permitting their huge stockpiling limit [3]. Multifunctional materials having both semiconducting and ferromagnetic properties at the same time, can conceivably cross over any barrier between information correspondence and information stockpiling gadgets. These various materials properties can exist together in undoped and change metal doped compound semiconductors, called weaken attractive semiconductors (DMS)[4, 5]. These materials open up the probability of coordinating the electron turn level of opportunity into the traditional charge-based electronic gadgets. This proposition to use both the electron turn and charge in electronic gadgets falls under the general title of "turn hardware" or "spintronics". Turn subordinate impacts in these spintronic gadgets can emerge from the cooperation of the turn of the accuse transporters of the attractive properties of the materials. This is required to prompt the advancement of cutting edge gadgets using turn level of opportunity together with ordinary microelectronics with a plausibility of sped up, lower power utilization, non-instability and expanded reconciliation densities [6]. One explicit necessity for acknowledging spintronic gadgets is the effective infusion of turn enraptured transporters into the semiconductors. Weaken attractive semiconductors may give much preferable turn infusion over ferromagnetic metallic anodes, since the impedance confound because of various electronic structure of attractive and semiconductor materials essentially upset the turn infusion process. Multi-useful spintronic materials having, for instance, a solid coupling between the electron turn and the optical reaction, may offer other potential applications including quantum bits for quantum teleportation, quantum calculation and correspondence, modulators, high recurrence working optical switches and so forth [6, 7].

Dielectric materials

One of the most broadly contemplated gatherings of fired materials has a place with the ferroelectrics. The ferroelectrics are the subgroups of dielectrics. Dielectric materials are electrical covers (i.e., they don't have free electrical charges under customary circumstances). Dielectrics are the materials where electrostatic field can continue for quite a while. These materials offer extremely high protection from the entry of direct present and subsequently, forcefully vary from metal, semiconductor and superconductors. A decent dielectric material ought to have high dielectric quality so they ought to have the option to

oppose high voltage without experiencing corruption as well as getting electrically leading. They ought to likewise have low dielectric misfortune in a rotating field. A few dielectrics can produce a potential contrast when exposed to mechanical pressure, or change physical shape if an outside voltage is applied over the material. This property is called piezoelectricity. Piezoelectric materials are another class of extremely helpful dielectrics. Some ionic gems and polymer dielectrics display an unconstrained dipole minute which can be turned around by a remotely applied electric field. This conduct is known as the ferroelectric impact. These materials are practically equivalent to the manner in which ferromagnetic materials carry on inside a remotely applied attractive field. Ferroelectric materials frequently have high dielectric constants, making them very helpful for capacitors. It is verifiable truth that dielectric properties of clay materials rely upon their synthesis, structure and test conditions. The dielectrics are electrical protecting materials, which can be enraptured by the use of electric field. Every one of the dielectrics are protectors yet every one of the encasings are not dielectrics. The ions and atoms of dielectrics are affected by an outer field and subsequently the positive charges are pushed toward the field while negative charges the other way from their harmony position. This development of inverse charges to inverse bearings brings about a dipole making its very own electric field. This procedure of creation of electric dipoles out of unbiased particles and atoms is referred to as polarization. Dielectrics might be comprehensively isolated into (I) polar dielectrics and (ii) non polar dielectrics.

- Polar (dipole) dielectrics-in polar dielectrics, a limited and changeless polarization known as unconstrained polarization (P_s), exist significantly after the expulsion of the applied electric field. Polar dielectrics are those in which the plausibility of focus concurring of the positive just as negative charge is very nearly zero (i.e., they don't match with one another). They all are of hilter kilter shape.

- Non-polar (nonpartisan) dielectrics-For the situation of non-polar dielectrics, there is no changeless or unconstrained polarization without an electric field. The focuses of both positive just as negative charges agree of each other, so the dipole snapshot of every atom in non-polar framework is zero. In this way singular atom after the utilization of electric field carries on as prompted dipole. Every one of those particles which have a place with this class are symmetric in nature.

MULTIFUNCTIONAL MAGNETIC SEMICONDUCTORS

Magnetic semiconductors exhibit both magnetic and semiconducting properties. One general approach to make a magnetic semiconductor is to replace a small fraction of cations in the non-magnetic parent semiconductor by magnetic ions, which produces a dilute magnetic semiconductor (DMS). A schematic representation of this process is shown in Fig. 1




Figure 1: A schematic representation of (a) a non-magnetic and (b) a dilute magnetic semiconductor

Hypothetical work by Dietl et al indicated that Mn doped GaN and ZnO could be ferromagnetic above room temperature, given certain materials suspensions. Abdominal muscle initio electronic structure computations by Sato et al have additionally anticipated ferromagnetic requesting experiencing significant change metal doped ZnO. These hypothetical outcomes impelled extra examination into DMS materials, prompting the revelation of various change metal doped semiconductors with ferromagnetism above room temperature. Broad work on different progress metal doped oxides including TiO₂, ZnO, In₂O₃, SnO₂ has been completed to scan for ferromagnetism, which has been seen at or above room temperature in a considerable lot of these frameworks. Re-markably, even undoped In₂O₃ has demonstrated high temperature ferromagnetism together with 55% turn polarization at low temperatures. While these DMSO frameworks have opened the plausibility of creating room temperature spintronic gadgets, the source of this ferromagnetism remains exceptionally dubious due the absence of reproducibility and huge varieties in the deliberate attractive properties in these materials. The fundamental riddle is whether the attraction in these frameworks is because of the consistently conveyed

change metal particles in the host lattice or because of the nearness of optional stages, including attractive debasement stage bunches. For conceivable mechanical uses of DMSs, it is imperative to comprehend the source of ferromagnetism in these frameworks. Various distinctive system have been proposed to clarify the beginning of ferromagnetism in DMSs.

ORIGIN OF MAGNETISM IN DILUTE MAGNETIC SEMICONDUCTORS

The DMSs can be considered as attractively latent host semiconductor with confined twists, emerging from dopants or surrenders. The host semiconductor may likewise be doped with either electrons or openings going about as versatile charge transporters, which can advance bearer interceded attraction in these frameworks. The attractive cooperations in these frameworks are typically dictated by the speed electronic trade, where the s and p orbitals have a place with the host and transporter benefactors and d orbitals to the change metal particles. Electronic trade associations through bearers in the conduction or valence groups in the framework may offer ascent to the attractive requesting.

NITRIDE COMPOUND SEMICONDUCTORS

Alloying a gathering III component with nitrogen (bunch V) delivers a nitride compound semiconductor, for example GaN, InN, AlN twofold combinations, InGaIn, InAlIn ternary compounds, or InGaAlN quaternary composites. Ongoing advancements in nitride semiconductors over other gathering III-V semiconductors open up the plausibility of full range strong state light sources, from infrared (IR) to the ultra violet (UV). Among these nitride semiconductors GaN, having a wide bandgap $E_g \sim 3.4$ eV, is one of the most contemplated semiconductors. This material has prompted the improvement of different lasing gadgets for example blue, green, and white light radiating diodes (LED) and laser diodes (LDs). Various unanswered inquiries remain concerning the properties of the paired compound InN, specifically the estimation of the band hole E_g . The recently acknowledged band hole estimation of InN was ~ 1.8 eV, is currently ascribed to different contributor abandons in the framework. The ongoing upgrades in the nature of InN tests recommends that the right band hole is $\sim 0.7-0.9$ eV [17, 18], which is in concurrence with the thickness utilitarian hypothetical (DFT) determined band hole esteems in the neighborhood thickness approximation (LDA) [19]. This new bandgap estimation of InN permits the $\text{In}_{1-x}\text{Ga}_x\text{N}$ strong arrangement to have band hole esteems running

from the infrared 0.7eV ($x=0$) to the bright 3.4eV ($x=1$), which would cover the whole sun based range. This wide band hole go for $\text{In}_{1-x}\text{Ga}_x\text{N}$ framework gives the likelihood to manufacture multi-intersection sun oriented cells covering the whole sun based vitality range. Another bit of leeway of nitride compound semiconductors over different semiconductors is that these are, all in all, high band hole materials (aside from InN), which might be helpful for high-power electronic gadgets. Also $\text{In}_{1-x}\text{Ga}_x\text{N}$ shows prevalent high vitality radiation opposition and compound obstruction, which make this framework favorable for space applications.

SEMICONDUCTORS AND THEIR CLASSIFICATIONS

Semiconductors are characterized as materials with an electrical resistivity (or conductivity) lying in the scope of 10^{-2} (10^2) – 10^8 (10^{-8}) Ohm.cm (mho.cm $^{-1}$). On the other hand, materials with a vitality hole (E_g) between a couple meV (underneath which warm excitations would create enormous control of directing states) and ~ 4 eV can likewise be viewed as semiconductors. Materials with a mostly filled conduction band having a limited electronic thickness of states at the Fermi level or an extremely little cover between conduction band and valence band with an insignificant thickness of states at the Fermi level are metals or semimetals individually, while those with a vitality hole more noteworthy than 4 eV are covers. These limits separating metals, semiconductors and protectors are not strongly characterized and there are exemptions to these general principles. For instance, aluminum nitride (AlN) and jewel are viewed as wide band hole semiconductors with $E_g \sim 6.2$ eV and 6eV separately, while GaAs is delegated semi-protecting with $E_g \sim 1.5$ eV. The schematic vitality band pictures of encasings, metals, and semiconductors are appeared in Fig 2.




Figure 2: Schematic energy band diagram for insulators, semiconductors and metals

This vitality band model characterizes semiconductors into two kinds direct band hole semiconductors and aberrant band hole semiconductors. Semiconductors having a similar worth k_{min} of the wave vector k (when all is said in done $k = 0$) for the most minimal vitality state in the conduction band and the most elevated vitality state in the valence band k_{max} for example the minima of conduction band and maxima of valence band lie at a similar k , are called direct bandgap semiconductors. These incorporate GaN, InN, and GaAs among others. A schematic E– k vitality band graph for direct bandgap semiconductors is appeared in Fig.3. (a). Semiconductors for which wave vector least k_{min} of the conduction band is not the same as the wave vector most extreme k_{max} of the valence band, that is the minima of the conduction band and maxima of the valence band don't have a similar k , are roundabout semiconductors, and incorporate Si and Ge. The schematic E – k vitality band outline for aberrant semiconductor is appeared in Fig 3.(b). Electrical conduction in an unadulterated semiconductor, regardless of whether immediate or aberrant, is expected to thermally produced natural charge transporters. These are in commonly extremely little in numbers, for instance just $\sim 10^9$ electrons/cm³ in silicon, and are just accessible in the conduction band at or above room temperature [13]. At extremely low temperatures, there will be no electrons in the conduction band of characteristic semiconductors. This clarifies why a characteristic semiconductor acts as an ideal cover near total zero. The property that makes semiconductors pertinent for some gadget applications is that their electrical conductivity can tuned by including little convergences of contaminations.




Figure 3: Schematic E-k diagram for (a) direct band gap semiconductor and (b) indirect band gap semiconductors

The kind of dopant utilized controls the conduction component in these materials. In the event that the dopant gives extra electrons to the host semiconductor, the framework is known as a n-type semiconductor, while if the dopants gives extra openings, the framework is known as a p-type semiconductor. When all is said in done, an exceptionally modest quantity, short of what one deformity particle for each million host molecules is adequate to change the semiconductor properties for gadget applications. These imperfections can be gainful or adverse to the properties of the semiconductor.

In an intrinsic semiconductor, the charge carriers are thermally activated and usually the electrons and holes are present in equal numbers. The electron and hole carrier concentrations in an intrinsic semiconductor are given by:

$$n = \int_{E_c}^{E_{top}} g_c(E) \times f(E) dE \quad (1)$$

And,

$$p = \int_{E_{bottom}}^{E_v} g_v(E) \times (1 - f(E)) dE \quad (2)$$

where $g_v(E)dE$, $g_c(E)dE$ are the number of valence and conduction band states per cm^3 in the energy range E and $E + dE$ and $f(E)$ and $(1 - f(E))$ are the probabilities that an available state at an energy E will be occupied by an electron or a hole. The integration in Eq (1) is taken from the bottom of the conduction band E_c to the top of the band while in Eq (2) the integral is taken from the bottom of the valence band to the top E_v . After simplifying the limits in the integral for Eqs (1) and (2) and using the Fermi-Dirac function $f(E)$ for the electron (or hole) distribution, these equations reduces to:

$$n = N_c \frac{2}{\sqrt{\pi}} F_{\frac{1}{2}}(\eta_c) \quad (3)$$

And,

$$p = N_v \frac{2}{\sqrt{\pi}} F_{\frac{1}{2}}(\eta_v) \quad (4)$$




Figure 4: Schematic E-k representation of non-degenerate and degenerate semiconductors

where $N_c = 2\left(\frac{m_n^* kT}{2\pi\hbar^2}\right)^{\frac{3}{2}}$ and $N_v = 2\left(\frac{m_p^* kT}{2\pi\hbar^2}\right)^{\frac{3}{2}}$ are the effective density of conduction and valence band states and $F_{\frac{1}{2}}(\eta)$ is the Fermi-Dirac integral of order $1/2$ and $\eta_c = \frac{(E_F - E_c)}{kT}$; $\eta_v = \frac{(E_v - E_F)}{kT}$ where E_F is the Fermi energy of the system. If the Fermi energy E_F lies in the range $E_v + 3kT \leq E_F \leq E_c - 3kT$, then the expression for n and p simplifies to:

$$n = N_c e^{\frac{(E_F - E_c)}{kT}} \& p = N_v e^{\frac{(E_v - E_F)}{kT}} \quad (5)$$

These expressions for n and p are valid if E_F lies in the conduction or valence band and no closer than $3kT$ to either band edge. When E_F is confined in this range, the semiconductor is called non-degenerate and whenever E_F lies within $3kT$ of either band edge the semiconductor is called degenerate. The schematic difference between non-degenerate and degenerate semiconductor is shown in Fig 4.

So far we have considered undoped intrinsic semiconductors, where number of electrons is the same as number of holes and their density can be written as:

$$n = p = n_i = (N_c N_v)^{\frac{1}{2}} e^{-E_g/2kT} \quad (6)$$

Where $E_g = E_c - E_v$ is the band gap. The concentration of charge carriers can be changed by introducing dopants leading to extrinsic semiconductors. The charges can be electrons, holes, positively charged ionized donors (which donate electrons to the conduction band), and negatively charged ionized acceptors (which donate holes to the valence band). Under equilibrium conditions the total charge due to extrinsic impurities and charge carriers is zero, that is, the system contains no net effective charge. This is known as the charge neutrality condition, even though charged entities are present everywhere in the semiconductor.

Mathematically charge neutrality condition is expressed as:

$$p - n + N_D^+ - N_A^- = 0 \quad (7)$$

where p, n, N_D^+ and N_A^- are the number of holes, electrons, positively charged donors and negatively charged acceptors per unit volume. Using the charge neutrality condition and the relation $n \cdot p = n_i^2$, the carrier concentrations n and p under non degenerate conditions for an extrinsic semiconductor are given by:

$$n = \frac{N_D - N_A}{2} + \left[\left(\frac{(N_D - N_A)}{2} \right)^2 + n_i^2 \right]^{\frac{1}{2}} \quad (8)$$

And,

$$p = \frac{n_i^2}{n} = \frac{N_A - N_D}{2} + \left[\left(\frac{(N_A - N_D)}{2} \right)^2 + n_i^2 \right]^{\frac{1}{2}} \quad (9)$$

These equations provide the electron and hole carrier densities in an extrinsic semiconductor. For intrinsic semiconductors $N_D = 0 = N_A$; substituting these into the equations above one find $n = n_i = p$ under equilibrium conditions. For n-type extrinsic semiconductors, where the excess electron charge carriers are provided by donor impurities, $N_D - N_A \simeq N_D \gg n_i$. Thus for n-type extrinsic semiconductors the previous equations for electron and hole concentrations become:

$$n \simeq N_D \& p \simeq \frac{n_i^2}{N_D} \quad (10)$$

and similarly for p-type extrinsic semiconductors, where the excess charge carriers are holes and are provided by acceptor impurities $N_A - N_D \simeq N_A \gg n_i$. In these materials the hole and electron carrier concentrations are given by:

$$p \simeq N_A \& n \simeq \frac{n_i^2}{N_A} \quad (11)$$

This flexibility in tuning the carrier concentrations and type of charge carriers in semiconductors make them useful for numerous microelectronic applications. In many cases, it is difficult to avoid introducing various defects during and subsequent to the fabrication process leading to highly degenerate systems. These accidental charge carriers cloak the intrinsic materials properties of the semiconductor and may make them unsuitable for the desired application. We will discuss the effect/influence of numerous defects introduced during and after the growth process for highly degenerate n-type InN and In₂O₃ compound semiconductors and will explore some possible application for these highly degenerate semiconductors.

MULTIFERROICS AND MICROSCOPIC ORIGIN OF MULTIFERROICITY

There was restored enthusiasm for multiferroics after N. Slope papers featuring that attraction and ferroelectricity are contraindicated because of the concoction incongruence of the physical source of these requesting marvels. By and large attraction emerges from the nearness of restricted electrons in halfway filled d or f shells of progress metal or uncommon earth particles.

The trade connection between these neighborhood minutes offers ascend to attractive requesting. On the other hand cations having void d-shells is required for ferroelectricity. For instance, the ferroelectricity in BaTiO₃ is expected (in enormous part) to the off kilter removal of Ti particle. This off kilter relocation is just conceivable since the Ti⁴⁺ particle has a vacant d-shell. This challenge is alluded as d 0 versus d n issue. In this manner, distinctive infinitesimal systems are important to clarify the beginning of ferroelectricity in multiferroic materials. D. Khomskii subdivided multiferroics into type-I and type-II multiferroics, in light of their attractive and ferroelectric requesting temperatures. Those multiferroics for which the ferroelectric and attractive requesting temperatures are all around isolated are named type-I multiferroics. In these multiferroics the causes of attractive and ferroelectric requesting are free and particular. Two significant and broadly examined instances of type I multiferroics are BiFeO₃ and YMnO₃. Multiferroics where the attractive request delivers the ferroelectricity, so that the ferroelectric requesting temperature agrees with an attractive change, are called type-II multiferroics. A few instances of type-II multiferroics are Ni₃V₂O₈, FeVO₄, TbMnO₃.

MULTIFERROICS WITH COLLINEAR MAGNETIC STRUCTURE

In this class of multiferroics, the Ferro power is driven by a collinear attractive stage. In this collinear attractive stage every single attractive minute are adjusted along a specific bearing without including the turn circle connection. The attractively initiated polarization in these frameworks is because of the trade striction in light of the fact that the attractive coupling shifts with nuclear positions. The as of late found Ca₃CoMnO₆ multiferroic display this conduct. This comprises of 1D chain of exchanging Co²⁺ and Mn⁴⁺ particles. Over the attractive requesting temperature, the separation between particles along chain is consistent, which doesn't support polarization. Be that as it may, beneath the attractive requesting temperature, a blend of rotating charge requesting of change metal particles of various valence, a comparable circumstance as clarified in "Electronic Ferro power" area, and an Ising-like attractive structure $\uparrow\uparrow\downarrow\downarrow$ can offer ascent to Ferro power through trade striction. This trade striction is because of rivalry between closest neighbor (NN) ferromagnetic and next closest neighbor (NNN) antiferromagnetic super trade associations.

CONCLUSION:

Materials that all the while display diverse physical properties give a rich region of research prompting the advancement of new gadgets. For instance, materials having a solid coupling among charge and turn degrees of opportunity are fundamental to understanding another class of gadgets alluded to for the most part as spintronics. Notwithstanding, these multifunctional frameworks present new logical difficulties in understanding the source and components for cross-control of various functionalities. Meager movies of In N nitride compound semiconductors and firmly related composites have been examined to comprehend the impacts of inborn deformities on the materials properties while considering potential utilizations of profoundly degenerate In N slight movies. As developed rf sputtered In N films on c-hub (0001) sapphire show profoundly degenerate n-type conduct because of oxygen absconds presented during development. The impact of oxygen In N grid has been additionally examined by purposefully including oxygen into the movies. These examinations affirm that oxygen is one of the principle wellsprings of giver electrons in degenerate In N. Over some basic grouping of oxygen, optional periods of In_2O_3 and In-O-N buildings were framed. It was likewise conceivable to tune the bearer fixation to create changes in the plasmon recurrence, which shifted from 0.45 eV to 0.8 eV. This trademark vitality scale recommends that these profoundly degenerate InN slim movies could be utilized for thermo photovoltaic cells, optical channels, and other IR electro-optic applications.

REFERENCES:

1. A. Dixit, G. Lawes, A. B. Harris, "Magnetic structure and magnetoelectric coupling in bulk and thin film FeVO_4 " Phys. Rev. B, 82, 024430 2010
2. A. Dixit, A. E. Smith, M. A. Subramanian, G. Lawes, "Magnetic suppression of multiferroic order in hexagonal $\text{YMn}_{1-x}\text{In}_x\text{O}_3$ ceramics" Solid State Communication, 150, 746 2010
3. J. S. Thakur, A. Dixit, Y. V. Danylyuk, C. Sudakar, V. M. Naik, W. J. Schaff, R. Naik, "Investigation of $\text{E}_1(\text{LO})$ phonon-plasmon coupled modes and critical points in $\text{In}_{1-x}\text{Ga}_x\text{N}$ thin films by optical reflectance measurements" Appl. Phys. Lett., 96, 181904 2010
4. C. Sudakar, A. Dixit, Sanjiv Kumar, M. B. Sahana, G. Lawes, R. Naik, V. M. Naik "Coexistence of anion and cation vacancy defects in vacuum annealed In_2O_3 thin films" Scripta Materialia, 62, 63 2010

5. A. Dixit, G. Lawes, “Development of electrical polarization at an antiferromagnetic transition in FeVO₄” J. Phys. Condens. Matter, 21, 456003 2009
6. A. Dixit, C. Sudakar, R. Naik, V. M. Naik, G. Lawes “Undoped vacuum annealed In₂O₃ thin films as a transparent conducting oxide” Appl. Phys. Lett., 95, 192105 2009
7. A. Dixit, Raghava P. Panguluri, C. Sudakar, P. Kharel, P. Thapa, I. Avrutsky, R. Naik, G. Lawes, B. Nadgorny “Robust room temperature persistent photoconductivity in polycrystalline indium oxide thin films” Appl. Phys. Lett., 94, 252105 2009
8. A. Dixit, C. Sudakar, J. S. Thakur, K. Padmanabhan, Sajiv Kumar, R. Naik, V. M. Naik, G. Lawes “Strong plasmon absorption in InN thin films” J. Appl. Phys., 105, 053104 2009
9. P. Kharel, A. Kumarasiri, A. Dixit, N. Rogado, R. J. Cava, G. Lawes “Scaling behavior of magnetic transition in Ni₃V₂O₈” Philosophical Magazine Letters, 89, 1923 2009
10. P. Kharel, C. Sudakar, A. Dixit, A. B. Harris, R. Naik, G. Lawes “Electric field control of a magnetic phase transition in Ni₂V₂O₈” Euro Physics Letters, 86, 17007 2009
11. A. Dixit, C. Sudakar, R. Naik, G. Lawes, J. S. Thakur, E. F. McCullen, G. W. Auner, V. M. Naik, “Phase separation and optical properties in oxygen rich InN films” Appl. Phys. Lett., 93, 142103 2008